

1

Unbox your weather station.

Attach antenna and, if applicable, attach anemometer, light sensor, bird guard and/or any external sensor(s).

(For 3230 Models, screw the stand post onto the base plate)

Scan to view the WatchDog 3000 Series Product Manual for more detailed instructions




2



3

Scan to install Watchdog Mobile on your phone or download from your App Store.



4

Open the weather station door and slide the power switch to the **ON** position. Wait 20 seconds for the station to power up.

Turn on the station's Bluetooth by pressing the **SELECT** button.

Release the button when LED turns on. LED will then flash continuously for 3 minutes.

5

Open the Watchdog Mobile app. Click on **BLUETOOTH**

Select the station's serial # from the list.

6

Click on the gear  icon which will take you to the configuration page.

Click on **OTHER** tab. Click on **WIFI SETTINGS**.

Enter SSID (network name) and Password.

Click **SAVE WIFI SETTINGS**.

7


Enter the station name. Enter latitude and longitude by clicking **USE MY LOCATION**.

Set the upload and logging intervals and time zone.

8

Click on **PORTS** tab and verify that all sensors are listed.

If additional sensors are connected, configure them from the drop-down menu.

Once completed, tap the save icon  in the top right corner.

9

If anemometer-equipped, select the station's serial # from the list again and then click the **OTHER** tab. A button will appear to **SET NORTH**.

Point the wind vane in the north direction and tap **SET NORTH**.

Upon **SUCCESS** tap **OK**.

10

Weather station is now set. Changes should appear in SpecConnect within the next 3 upload intervals.

11

If you have additional questions on set-up/assembly, please scan the QR code to the right for detailed video instructions.

12

