

QUICK START GUIDE

FIELDSCOUT[®] SOIL METER CELL PHONE HOLDER



ITEM #: 6050

QUICK START GUIDE: **FIELDSCOUT® SOIL METER CELL PHONE HOLDER**

STEP 1: REMOVE PARTS FROM THE BOX



The FieldScout Cell Phone Holder is made of three separate components:

1. Soil Meter Mounting Bracket
2. Adjustable Cell Phone Holder
3. Adjustable Mounting Clip



STEP 2: COMBINE PHONE HOLDER PARTS



Unscrew the nut from the back of the phone holder (2). Place the nut onto the mounting clip (3) with the threads facing out.



Line up the ball joint of the mounting clip (3) with the ball socket on the phone holder (2). Push to click in place, then tighten the nut.



Turn the knob on the mounting clip (3) to extend the hook fully.



Insert the hook into the connection slot on the soil meter bracket (1) as shown. Tighten the knob to secure the assembled phone holder in place.

QUICK START GUIDE: **FIELDSCOUT® SOIL METER CELL PHONE HOLDER**

STEP 3: CONNECT BRACKET TO SOIL METER AND MOUNT CELL PHONE



Loosen the bolt on the soil meter bracket (1) by turning the thumb knob counter-clockwise.



Slip the bracket over your FieldScout soil meter (compatible with the TDR350 and SC950). Tighten the bolt to secure bracket.



Press the release button on the back of the phone mount (2) to extend the mounting arms to the correct width to fit your phone.



Squeeze the extended arms to secure your phone to the mount. Adjust the angle of the phone mount for the best viewing while using your soil meter.

STEP 4: ENJOY MEASURING SOIL MOISTURE AND COMPACTION

